

Repacement Bulbs	
Description	
Part Number	MR16, 3watt, Warm white
	MR16-3W-WW
CRI	
View Angle	>60
Colour temperature in degrees Kelvin CT	30°/38°/45°/60°
Optical efficacy in lumens/watt	2,500K-5,000K
Luminous flux in lumens	36.5 Lm/W
Power consumption in watts	117 Lm
Life cycle	3.2W
Input voltage range	50,000 hrs
Operational temperature	12~15V AC/DC
Operational humidity	-10 deg. C ~ +45 deg. C
Number of devices (led)	10% ~ 95%
Physical size	1pc (3W per led)
	Φ50mm*45mm
Description	
Part Number	GU10-3watt, Warm White
	GU10-3W-WW
CRI	
View Angle	> 60
Colour temperature in degrees Kelvin CT	30°/38°/45°/60°
Optical efficacy in lumens/watt	2,500K-5,000K
Luminous flux in lumens	36.5 Lm/W
Power consumption in watts	117 Lm
Life cycle	3.2W
Input voltage range	50,000 hrs
Operational temperature	85~265V AC
Operational humidity	-10 deg. C ~ +45 deg. C
Number of devices (led)	10% ~ 95%
Physical size	1pc (3W per led)
	Φ50mm*52mm